



## TECHNICAL SHEET FA 40 902 20

### WORK POSITIONING KERNMANTLE LANYARD WITH RING ADJUSTER



Work positioning kernmantle lanyard with ring adjuster

- Made up of 12mm diam polyamide kernmantle rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Sewings protected under a strong protective sleeve which allow a visual checking of the sewings.

**Connectors:** 1 steel screw-locking karabiners opening 17 mm, ref. FA 50 101 17, and 1 snap hook opening 17 mm, ref. FA 50 202 17.

**Compliance:** EN358:1999.

#### Material of components:

Lanyard: polyamide

Connector: steel

Ring adjuster: forged alloy steel.

<b>Size:</b>		<b>Weight:</b>
Maximum length : 2 mtrs		0.69 kg

#### **KRATOS SAFETY**

689 Chemin du Buclay  
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

<b>HS CODE</b>
56075090
<b>CARTON SIZE / PCS.</b>
80 x 40 x 24 / 20
<b>AET N°2789 I6 E4</b>
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>ARTICLE 11 GB07/73551</b>
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom